

# TOTO®

Perfection by Design

## TOTO'S® ECOPOWER FLUSH VALVES™ Sensor Toilet Flush Valve, Exposed - 1.6 GPF

To be specified:

### Sensor Toilet Flush Valve

- ☐ Complete Set, Nickel Chrome Plated Finish
  - ☐ TET1GNC-32 (1-1/2" V.B.) - Left and Right Rough
- Complete set supplied with:
  - ☐ Vacuum Breaker & Angle Stop Set - VB9CP-32
    - ☐ 1" Angle Stop - 10077t3
    - ☐ 1-1/2" Vacuum Breaker - 10075t1
    - ☐ Spud Nut & Escutcheon - 71051Nt6
    - ☐ Sweat Solder Kit - TH559EDVSJ3

- ☐ Valve only, Nickel Chrome Plated Finish
  - ☐ TET1GNC - Left and Right Rough

Z-4000-J - Adapter for Ground Joint Angle Stops  
10075T1L - 24" Long 1-1/2" vacuum breaker tube

*Meets the American Disabilities Act Guidelines and ANSI A117.1 requirements for people with disabilities.*



TET1GNC-32

### AUTOMATIC FLUSHING SYSTEM

TOTO, the world leader in advanced plumbing systems, provides sensor operated flush valves for facilities demanding the finest sanitation equipment for busy restrooms. "Hands-free" technology effectively reduces unsanitary conditions from unflushed fixtures.

### SELF-GENERATING POWER SYSTEM

TOTO's new technology of automatic generator flush valves offer easy installation without the cost and downtime required to install power supplies and wiring for each valve. A hydro-powered turbine charges the power supply during usage eliminating the need for a battery replacement or consumption of external power for up to 10 years.

### SUPERIOR PISTON VALVE

TOTO's piston valve technology is a marked improvement over traditional rubber diaphragm type valves. Longer piston travel and SELF-CLEANING 360° debris screen reduce common problems such as continuous running and flooding. The piston seat itself will not warp or mis-seal thus, significantly reducing repair and maintenance costs. A micro-porous cup seal keeps the piston self-lubricated upon each activation with the incoming water supply.

### NEUTRAL ROUGH-IN

TOTO's sensor flush valve has neutral rough-in, it can be used as right or left rough-in with no modification.

**OPERATING PROCEDURE** A sanitary environment without using the hands.

1 Infrared Sensor	2 Flushing	3 Flushing Every 24 Hours	4 Manual Flushing Button
The infrared sensor detects a user sitting on the toilet seat, or standing.	When the user stays in place longer than 6 seconds then moves away, the controller sends a signal to the operating unit to automatically trip the flush valve.	If toilet is not used, the system automatically flushes every 24 hours as a maintenance and hygienic precaution.	Use the manual flush button for maintenance and/or emergencies.




Item No	Description
07923	TOTO ECOPOWER TOILET VALVE 1.28 TET1LN32-

# TOTO'S® ECOPOWER FLUSH VALVES™

## Sensor Toilet Flush Valve, Exposed - 1.6 GPF

### SPECIFICATIONS

Product	TET1GNC- Valve Only, Left and Right Rough, Chrome Plated Finish
	TET1GNC-32- Complete Set (1-1/2" V.B.), Left and Right Rough, Chrome Plated Finish
Power supply	Hydro-Power Charge, 10 years based on 2,000 cycles per month (Backup battery: 4 years at 4,000 cycles per month without recharging)
Supply water pressure	15 psi - 125 psi*
Water supply pipe	1" NPT
Discharge quantity	Factory setting at 1.6 GPF/6.0 LPF
Ambient temperature	32°-104°F (0°-40°C)
Trap seal protection	Automatic flushing once every twenty-four (24) hours, if not used
Detection time	Factory setting at six (6) seconds minimum
Detection range	Self-adjusting to environment
Warranty	Limited three (3) year warranty on all component parts. Details available upon request.
Listings	 A.S.S.E. 1037

These dimensions and specifications are subject to change without notice.

\*Water pressures over 80 psi are not recommended for most plumbing fixtures.

U.S. Patent Pending

### SUGGESTED ENGINEERING SPECIFICATION:

TOTO Model No. \_\_\_\_\_  
Automatic infrared sensor activated, piston toilet flush valve.  
Heavy-duty zinc die cast cover with nickel chrome finish.  
Vandal resistant hex head screws. Automatic sensor adjustment  
on installation. Manual override button. Piston valve and

solenoid with self-cleaning mechanism. Automatic flush every twenty four hours if not used. Angle stop and vacuum breaker included with accessories. Through the use of TOTO's® EcoPower Flush Valves™, using the valve 2000 times a month will fully recharge the valve for up to 10 years.

### DIAGRAM:

